



product: **LUBRICANT ULTRA F5**

**Description**

New generation technical spray, loosener, waterproof, protective lubricant and degreaser of mechanical components.

**Application Areas**

Its exclusive multipurpose properties make F5 ULTRA the perfect partner at work and home. Perfect at workshop as well as for bricolage. Thanks to its penetrating and loosening power, it has many applications; very good lubricant; eliminates electricity dispersions removing humidity and avoiding short circuits. Avoids and stops corrosions dissolving rust; protects and lubricates padlocks, locks, cars, motorbikes and bicycles mechanical parts, electronic engine components, electric appliances, switches, hinges. Easily removes grease, tar and glue from metallic and plastic surfaces; keeps outdoor switches and mechanical equipments efficient.

**Packing**

Spray can - 400 ml

**Technical Data**

Colour	Dark Brown
Appearance	Liquid
Specific Gravity	ca. 0,64 Kg/l
Flash Point (G.P.L.)	< -50 °C
Can Pressure	3,2 bar
Solubility:	in solvents
Application temperature	5 ÷ 30 °C

**Instruction for use**

Shake well before use. The "Multiposition" valve allows spraying at 360°. Its special straw nozzle allows a direct and accurate spray as well as a "fan" application. Spray the product at a distance of about 20 cm from surface, at small intervals, to let it act for a few minutes and penetrate deeply.

**Warnings**

*Product classified as hazardous (see relevant Material Safety Data Sheet).*

*Specific Warning: Pressurized container. Protect from sunlights and do not expose to temperature exceeding 50°C. Do not pierce nor burn even after use. Do not spray on a naked flame or incandescent material.*

**Shelf-life**

18 months in original, unopened packing (temperatures between 5 and 30°C).

**Notes**

*For further information regarding safety and handling refer to the Safety Data Sheet. The information given in our circulars are at the best of our knowledge. They show possible uses of our products without any obligation.*