



Technical Data

set-15

product: Color Point - ACRYLIC ENAMEL

<u>Description</u> Fast drying paint, based on Acrylic modified resins.

Application areas

Suitable for fixing, decoration, retouching and finishing of any kind of paintable

surfaces, for inside and outside applications.

After curing, it provides an elastic and very resistant coating to scratches, yellowing,

corrosion and weathering.

Packing 400 ml spray can

<u>Technical</u> Colour: various

<u>Data</u> Viscosity/20°C: 12 sec. F4
Can pressure: (23°C) 4 bar

 Skinforming time/20°C:
 5 - 8
 min.

 Tack-free time/20°C:
 15 - 20
 min.

 Drying time/20°C:
 12 - 20
 hours

 Brightness:
 80 - 85
 Gloss

Yield: 0,95 - 1,1 mg/400ml

<u>Instrctions</u> Surfaces must be completely clean, dry, free of grease and rust. Eventually remove

presence of old paint by sanding softly. Before use, shake can for at least 2 minutes. Spray several layers at a distance of 25 cm. If necessary, to get a better coating,

spray again after 5 minutes.

After use, turn the can upside-down and press the valve for about 3 seconds to

remove enamel residues.

<u>Classification</u> Product classified as Dangerous (see Material Safety Data Sheet).

Additional warning: Pressurized container: protect from sunlight and do not expose to

temperatures exceding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Shelf life 18 months from production date, in original packing, at cool and dry place

Notes For further information regarding safety and handling refer to the Safety Data Sheet.

The information given in our circolars are at the best of our knowledge.

They show possible uses of our products without any obbligation.

PIGAL s.r.l. Via G. Rossa, 2 40053 VALSAMOGGIA Crespellano (Bo) - I Tel. +39 051 969068, Fax. +39 051 969353 sigill@pigal.it - www.pigal.it